

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



\* For Examiner Reference

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

Claims 1 – 13: Cancelled

14. (New) A stator for an eccentric screw pump or an eccentric worm motor, comprising:

an outer tube (1) that is provided with a lining (6) of elastomeric material and has a hollow space or cavity, in the shape of a double or multiple spiral, for accommodating a rigid rotor that is also in the form of a spiral, wherein said stator has one spiral more than does said rotor, and wherein said outer tube (1) has a configuration such that a thickness of said lining (6) is at least nearly uniform; and

two inner tubes (2, 3) disposed in said lining 6, wherein said inner tubes are respectively provided with apertures (4,5)

15. (New) A stator for an eccentric screw pump or an eccentric worm motor having a stator, comprising:

an outer tube 1 that is provided with a lining (6) of elastomeric material and has a hollow space or cavity, in the shape of a double or multiple spiral, for accommodating a rigid rotor that is also in the form of a spiral, wherein said spiral of said stator has one spiral more than does said rotor; and

a sealing ring (10, 20) disposed at an end face of said lining (6), wherein said sealing ring seals a transition from said lining to said outer tube (1).

16. (New) A stator according to claim 14, wherein said inner tubes (2, 3) are made of metal.

17. (New) A stator according to claim 14, wherein a size and number of said apertures 4, 5 of said two inner tubes 2, 3 differ.

18. (New) A stator according to claim 14, wherein a second one of said inner tubes 3 is disposed in a first one of said inner tubes 2, wherein said apertures 5 of said second inner tube 3 have a smaller diameter than do said apertures 4 of said first inner tube 2, and wherein said second inner tube 3 is provided with a greater number of apertures 5 than is said first inner tube 2.

19. (New) A stator according to claim 14, wherein inner one of said inner tubes 3 is surrounded by a hose of elastomeric material rather than by the other one of said inner tubes 2.

20. (New) A stator according to claim 19, wherein said elastomeric material is rubber.

21. (New) A stator according to claim 19, wherein said hose is provided with apertures.

22. (New) A stator according to claim 15, wherein said sealing ring 10, 20 is connected with said outer tube 1 via welding.

23. (New) A stator according to claim 15, wherein a press fit exists between said sealing ring 10, 20 and said outer tube 1.

24. (New) A stator according to claim 15, wherein sealing ring 10, 20 is provided with a conical section 12, 24 that is spaced from an inner surface of said outer tube 1 and opens in a direction toward an interior of said stator and toward said lining 6.

25. (New) A stator according to claim 15, wherein said sealing ring 10 is provided with a sealing bead 13 on an end of said sealing ring that faces said lining 6.

26. (New) A stator according to claim 15, wherein a clamping ring 15 is disposed on said sealing ring 10 and presses said sealing ring against said lining 6.

27. (New) A method for producing the stator of claim 1, including the steps of:  
producing said outer tube 1 and said inner tubes 2, 3 from cylindrical tubes;  
fitting said outer tube 1 and said inner tubes 2, 3 together and then  
interconnecting them; and subsequently  
imparting said outer tube 1 and said inner tubes 2, 3.